



The McCloskey 512 trommel screener combines high production rates, versatility, and ease of use in one package. It is extremely popular with topsoil producers, excavating contractors, and quarry owners. The McCloskey 512 is available in both radial or extended fines conveyor models and with a remote controlled hydraulic tipping grizzly. New option for 2005 – rubber drum extension.

## Features, Benefits, and Options

- Four lifting bars on drum provide aggressive screening action
- Patented remote controlled 180° radial stockpiling conveyor with a variable discharge height for maximum stockpiling flexibility
- Tow bar for easy on-site mobility
- Drum exchange system for maximum versatility
- Remote controlled hydraulic tipping grizzly
- Quick and easy set up and tear down with no tools required
- All belts and drum feature reversible operation



Specifications (512 with radial conveyor)	
Engine:	80 HP (60 kw) Caterpillar diesel engine
Hopper:	4 ft. 9 in. wide x 12 ft. 6 in. long (1.45 m x 3.81 m)
Screen:	5 ft. diameter x 12 ft. long (1.5 m x 3.66 m)
Weight:	30,360 lbs (13,771 kgs)
Transport Height :	13 ft. 6 in. (4.1 m)
Transport Length:	42 ft. 3.5 in. (12.88 m)
Transport Width:	8 ft. 3 in. (2.5 m)

Specifications vary with screener options and are subject to change without notice.



SOUTHEAST CRUSH & SCREEN LLC  
615 289 9890